



1" - 3/4"



2" - 1-1/2"



ADUP

- R-10 through R-65
- RE21S through RE65S
Class I, Div. 1 & 2, Groups A,B,C,D
Class I, Zone 1, Groups IIC, IIB, IIA
Class II, Div. 1 & 2, Groups E,F,G
- R-73 through R-109
Class I, Div. 1 & 2, Groups A,B,C,D
Class I, Zone 1, Groups IIC, IIB, IIA
Class II, Div. 1 & 2, Groups E,F,G

UL Standard: 886

CSA Standard: C22.2 No. 30

Listed File No. E 10514

Certified File No. LR11716

FEATURES-SPECIFICATIONS

Application

- To reduce the trade size of a taped hole or hub.

Features

- Tapered threads (NPT)
- Smooth internal bushing protects conductors
- Threaded for Rigid Conduit or IMC

Material/Finish

Copper-free Aluminum
(less than 4/10 of 1%)
(R-10 through R-109)

Natural Finish

Steel/Zinc Plated

(RE21S through RE65S)

| REDUCING BUSHINGS | | | |
|-------------------|-------|-----------------|-------------|
| CATALOG NUMBER | | HUB SIZE | DIMENSIONS |
| KILLARK ALUM. | STEEL | | BODY LENGTH |
| R-10 | — | 1/2" — 3/8" | 5/8"(16) |
| R-20 | — | 3/4" — 3/8" | 7/8"(22) |
| R-21 | RE21S | 3/4" — 1/2" | 23/32"(18) |
| R-30 | — | 1" — 3/8" | 7/8"(22) |
| R-31 | RE31S | 1" — 1/2" | 23/32"(18) |
| R-32 | RE32S | 1" — 3/4" | 23/32"(18) |
| R-41 | RE41S | 1-1/4" — 1/2" | 13/16"(21) |
| R-42 | RE42S | 1-1/4" — 3/4" | 13/16"(21) |
| R-43 | RE43S | 1-1/4" — 1" | 13/16"(21) |
| R-51 | RE51S | 1-1/2" — 1/2" | 13/16"(21) |
| R-52 | RE52S | 1-1/2" — 3/4" | 13/16"(21) |
| R-53 | RE53S | 1-1/2" — 1" | 13/16"(21) |
| R-54 | RE54S | 1-1/2" — 1-1/4" | 13/16"(21) |
| R-61 | RE61S | 2" — 1/2" | 7/8"(22) |
| R-62 | RE62S | 2" — 3/4" | 7/8"(22) |
| R-63 | RE63S | 2" — 1" | 7/8"(22) |
| R-64 | RE64S | 2" — 1-1/4" | 7/8"(22) |
| R-65 | RE65S | 2" — 1-1/2" | 7/8"(22) |
| R-73 | — | 2-1/2" — 1" | 1"(25) |
| R-75 | — | 2-1/2" — 1-1/2" | 1"(25) |
| R-76 | — | 2-1/2" — 2" | 1"(25) |
| R-85 | — | 3" — 1-1/2" | 1-1/4"(32) |
| R-86 | — | 3" — 2" | 1-1/4"(32) |
| R-87 | — | 3" — 2-1/2" | 1-1/4"(32) |
| R-97 | — | 3-1/2" — 2-1/2" | 1-3/8"(35) |
| R-98 | — | 3-1/2" — 3" | 1-3/8"(35) |
| R-106 | — | 4" — 2" | 1-1/2"(38) |
| R-107 | — | 4" — 2-1/2" | 1-1/2"(38) |
| R-108 | — | 4" — 3" | 1-1/2"(38) |
| R-109 | — | 4" — 3-1/2" | 1-1/2"(38) |

| ADUP ADAPTERS | |
|-----------------|------------------------|
| CATALOG NUMBER① | DESCRIPTION |
| ADUP-01 | MALE 3/8 FEMALE 1/2 |
| ADUP-12 | MALE 1/2 FEMALE 3/4 |

① Series ADUP suitable for Class I, Groups A,B,C,D

Material/Finish

Copper-free Aluminum
(less than 4/10 of 1%)

Natural Finish



KILLARK®