

Lanyards and Anchorage Connectors

MSA Workman Energy-Absorbing Lanyards

Energy-absorbing lanyards provide a means of connection between the fall arrest attachment of MSA full body harnesses and a qualified anchorage and anchorage connector. The energy absorber keeps fall arrest forces below EN limits and deceleration distance is controlled to a maximum of 175 cm. The lanyard is available in web and kernmantel rope configurations with a variety of snaphooks.

MSA Workman energy-absorbing lanyards are lightweight with a low-profile body. The energy absorber includes a clear, durable protective cover over the labels to increase service life and allow for easy inspection.

- Tear-tape design to keep fall arrest forces below 6 kN
- Choice of single or twin-leg configurations
- Choice of connector configurations
- Certified to EN 354, EN 355


Variants



Single-Leg, webbing,
steel screwgate carabiners



Single-Leg, kernmantel rope,
steel screwgate carabiners



Twin-Leg, webbing,
steel screwgate carabiners



Twin-Leg, kernmantel rope,
steel screwgate carabiners

Other connections ...

- Aluminium screwgate carabiner (1)
- Aluminium snaphook (2)
- Steel scaffold hook (3)
- Aluminium scaffold hook (4)
- Aluminium autolock carabiner (5)

... to anchorage



... to harness



MSA Workman Restraint Lanyards

Restraint lanyards are primarily used for travel restriction (to restrain a worker from reaching a fall hazard) and work positioning (stabilizing a worker at an elevated location) applications. It connects the anchor point with the body harness and should never be used to arrest a fall.

To meet all your application needs and environments, MSA Workman Restraint Lanyards are available in web and kernmantel rope.

Certified to EN 358.



Kernmantel Rope, Aluminium Carabiner



Webbing, Steel Screwgate Carabiner



MSA Workman Anchorage Sling

Anchorage Connectors are compatible for use with MSA fall arrest and confined space entry/retrieval components. They have a minimum breaking strength of 22.24 kN.

- 25 mm webbing
- 1.5 m or 2 m lengths available
- Certified to EN 354, EN 795

MSA Workman PFL EN Self-Retracting Lanyards

Self-Retracting Lanyards are fast-acting fall arresters that limit free fall distance, deceleration distance and free fall forces while allowing the user freedom of movement.

With its solid design and fast-acting brake mechanism, you can be confident that the MSA Workman Personal Fall Limiter (PFL) will be there for you when you need it most. It is ideal for climbing ladders or any other application where vertical mobility is needed.

- Integral load indicator
- Integral swivel at PFL/SRL connector
- Durable, engineered thermoplastic housing
- Certified to EN 360



Lanyards

MSA Workman Energy-Absorbing Lanyards					
Part No. Single-Leg	Part No. Twin-Leg	Material	Length	Harness Connection	Anchorage Connection
10115741	10115750	Webbing	2.0 m adjustable	Steel screwgate carabiner	Steel screwgate carabiner
10115742	10115751	Webbing	2.0 m adjustable	Steel screwgate carabiner	Steel scaffold hook
10115745	10115754	Webbing	2.0 m adjustable	Aluminium screwgate carabiner	Aluminium screwgate carabiner
10115747	10115756	Webbing	2.0 m adjustable	Aluminium screwgate carabiner	Aluminium scaffold hook
10115748	10115757	Webbing	2.0 m adjustable	Aluminium screwgate carabiner	Aluminium snaphook
10115749	10115758	Webbing	2.0 m adjustable	Aluminium autolock carabiner	Aluminium autolock carabiner
10115759	10115777	Kernmantel rope	1.5 m fixed	Steel screwgate carabiner	Steel screwgate carabiner
10115760	10115778	Kernmantel rope	1.5 m fixed	Steel screwgate carabiner	Steel scaffold hook
10115763	10115781	Kernmantel rope	1.5 m fixed	Aluminium screwgate carabiner	Aluminium screwgate carabiner
10115765	10115783	Kernmantel rope	1.5 m fixed	Aluminium screwgate carabiner	Aluminium scaffold hook
10115766	10115784	Kernmantel rope	1.5 m fixed	Aluminium screwgate carabiner	Aluminium snaphook
10115767	10115785	Kernmantel rope	1.5 m fixed	Aluminium autolock carabiner	Aluminium autolock carabiner
10115768	10115786	Kernmantel rope	2.0 m fixed	Steel screwgate carabiner	Steel screwgate carabiner
10115769	10115787	Kernmantel rope	2.0 m fixed	Steel screwgate carabiner	Steel scaffold hook
10115772	10115790	Kernmantel rope	2.0 m fixed	Aluminium screwgate carabiner	Aluminium screwgate carabiner
10115774	10115792	Kernmantel rope	2.0 m fixed	Aluminium screwgate carabiner	Aluminium scaffold hook
10115775	10115793	Kernmantel rope	2.0 m fixed	Aluminium screwgate carabiner	Aluminium snaphook
10115776	10115794	Kernmantel rope	2.0 m fixed	Aluminium autolock carabiners	Aluminium autolock carabiner
MSA Workman Restraint Lanyards					
Part No.	Material	Length	Connection		
10115795	Webbing	1.5 m fixed	Steel screwgate carabiner		
10115796	Webbing	1.5 m fixed	Aluminium screwgate carabiner		
10115797	Webbing	2.0 m fixed	Steel screwgate carabiner		
10115798	Webbing	2.0 m fixed	Aluminium screwgate carabiner		
10115799	Webbing	2.0 m adjustable	Steel screwgate carabiner		
10115800	Webbing	2.0 m adjustable	Aluminium screwgate carabiner		
10115801	Kernmantel rope	2.0 m adjustable	Aluminium carabiner		
MSA Workman PFL EN Self-Retracting Lanyards					
Part No.	Material	Length	Lifeline Connection	PFL Connection	
10119078	Cable	3.6 m	Steel snaphook	None	
10119079	Cable	3.6 m	Aluminium snaphook	None	
10119080	Cable	3.6 m	Aluminium carabiner	None	
10119081	Cable	3.6 m	Steel scaffold hook	Back d-connector	

Anchorage Connectors

MSA Workman Anchorage Sling		
Part No.	Material	Length
10115802	Webbing	1.5 m adjustable
10115803	Webbing	2.0 m adjustable